



BIGUMA®-Hakenband

Fusible, bituminous joint tape with innovative cross-sectional design

Uses

BIGUMA®-Hakenband is a fusible joint tape with an innovative cross-sectional design. The special shape of the top profile edge allows precise positional fixing, simplifying the installation process. BIGUMA®-Hakenband is used to seal joints in asphalt roads as they are created during new construction, maintenance projects and excavation work.

Standards: TL Fug-StB

Properties

- defined and precise positional fixing makes installation easier
- no additional positional stabilisers required
- optimised material distribution to the cold side, creating the perfect rivet head
- top edge of the profile determines the height of the rolled asphalt to be sealed

Application instructions

Substrate preparation

The joint surfaces must be dry, clean and free from dust and loose debris. Apply primer COLZUMIX®-Haftgrund to both joint faces by brush or spray; avoid overdosing. Allow to dry before placing the tape.

Application

Position BIGUMA®-Hakenband in the joint so that the hook profile edge aligns with the finished road level — this edge sets the height for the asphalt layers to be rolled. Lightly melt the tape with a propane gas torch and press firmly onto the primed substrate. The innovative cross-sectional shape distributes material optimally toward the cold side of the joint, forming a well-sealed rivet head without additional positional stabilisers.

Cleaning agents

Equipment: BIGUMA®-SWS, petrol or commercial solvents

Skin contact: hand washing paste

Form of supply

28 m per carton, 24 cartons per pallet.

Technical data

Approvals	TL Fug-StB
-----------	------------

www.biguma.lt | info@biguma.lt



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.