

BIGUMAtor® -MB



Machine for applying BIGUMA®- M Band



Use

This hand-held machine has been designed to facilitate the application of BIGUMA®- M Band in multiple dimensions for the sealing of asphalt surface joints. The machine can be operated by a single person. When the operating temperature is reached, the cartridge is fitted with the joint tape with its tip inserted into the extruder.

BIGUMAtor®- MB is placed after the first discharge of the material at the joint surface to be sealed. Align the outlet nozzle with the joint surface – it can be adjusted by means of a support wheel. To ensure better alignment/overview, use the swivel-mounted plumb bob on the front end of the BIGUMAtor®- MB.

Technical Data

Length:	2.650 mm
Width:	860 mm
Height:	1.160 mm
Weight:	430 kg, empty
Motor:	Honda ECT7000P single-cylinder four-stroke engine with overhead valves
Tank:	6,5 l - unleaded gasoline
Max. output:	5,6 kVA/50Hz
Measured sound power level:	96 dB
Fuel consumption:	2,7 l/h
Travel speed:	Max .1 m/s
Operating temperature:	85 °C

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de

Producer

Plant Dortmund



Additional information

Extruder and travel speed can be adjusted via the designated switch.

BIGUMator®- MB is CE marked.

Prior to applying the joint tape, a suitable primer, such as COLZUMIX®- Haftgrund, should be applied.

Joint tape is not included in the scope of supply.

Follow the instructions in the operator's manual!

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 03/19

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de

Producer

Plant Dortmund