



PROXAN®-CP-G

Low-viscosity primer for polysulphide sealants on non-absorbent substrates

Uses

Our transparent, low-viscosity primer PROXAN®-CP-G is intended for use on non-absorbent substrates. Whether split clinkers, glazed ceramic, plastic (PVC, polyester, melamine resin), metal (aluminium, steel, copper, zinc) or glass, PROXAN®-CP-G significantly improves the adhesion of the sealant.

Properties

- Alkyl silane based
- Suitable for non-absorbent substrates
- Excellent adhesive properties

Application instructions

Application

The substrate must be dry, free of dust and grease and without any loose components. Old coatings must be removed. The primer must be uniformly applied using a brush. After a flash-off time of 10 to 30 minutes the sealant can be introduced.

Material consumption

0.005 to 0.01 l per linear metre (depending on joint dimensions)

Storage

Can be stored for 12 months in a dry location at temperatures below +25 °C in a closed original container.

Form of supply

Metal bottle 400 ml: 18 bottles per carton

Technical data

Chemical basis	alkyl silane
Processing time (flash-off time)	10 to 30 minutes
Colour	water clear
Density	approx. 0.8 g/ml
Consumption	0.005–0.01 l/linear m (depending on joint dimensions)

www.biguma.lt | info@biguma.lt



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.