



DOBAU®-2SA Dichtungsband

Double-sided adhesive bitumen sealing strip

Uses

DOBAU®-2SA Dichtungsband is a double-sided adhesive sealing and installation strip made of polymer-modified bitumen, specifically developed for reliable waterproofing in above- and below-ground construction. As an ideal complement to the DOBAU®-Abdichtungsbahn KSK, it provides a permanently tight bond even in particularly demanding connection areas.

Thanks to its high adhesive strength, the tape enables secure application following the "mass-on-mass" principle and is well suited for sealing longitudinal and transverse joints, wall-floor transitions, internal and external corners, edges, coves, and complex details such as pipe penetrations or floor drains. It can also be used to fix insulation and drainage boards, and for coating on expansion joint strips.

DOBAU®-2SA Dichtungsband is designed for both vertical and horizontal applications: walls, floor slabs, foundations, plinths and basement walls, concrete foundations, underground garages. Compatible substrates include smooth concrete, masonry, screeds and OSB boards.

Properties

- simple application — peel first release film, then remove the silicone-coated backing paper in a second step
- self-adhesive on both sides, good crack bridging and levelling of minor surface irregularities
- excellent for bonding insulation boards to the DOBAU®-Abdichtungsbahn KSK and for fixing expansion joint strips
- ideal as reinforcement at corners, surface transitions, pipe, duct and cable penetrations in basement waterproofing
- primer-free application from +5 °C to +40 °C

Application instructions

Application

Suitable for improved bonding of longitudinal and transverse joints under the DOBAU®-Abdichtungsbahn KSK ("mass-on-mass" principle), at wall-floor transitions, internal and external corners, edges, coves, expansion joint strips and complex details such as pipe penetrations and floor drains. Also usable for fixing insulation and drainage boards and as a coating on expansion joint strips. Apply to vertical and horizontal substrates (walls, floor slabs, foundations, plinths, basement walls, underground garages) of smooth concrete, masonry, screed or OSB boards.

Form of supply

Width: 300 mm, length: 10 m. Other dimensions available on request.

Technical data

Material thickness	1.0 mm (other variants 0.5–2.5 mm available on request)
Standard width	300 mm (other dimensions on request)
Standard length	10 m (other dimensions on request)
Processing temperature	+5 °C to +40 °C

www.biguma.lt | info@biguma.lt



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.