



# BIGUMA®-Hakenband

Fusible, bituminous joint tape with innovative cross-sectional design

---

## Uses

---

BIGUMA®-Hakenband is a fusible joint tape with an innovative cross-sectional design. The special shape of the top profile edge allows precise positional fixing, simplifying the installation process. BIGUMA®-Hakenband is used to seal joints in asphalt roads as they are created during new construction, maintenance projects and excavation work.

**Standards:** TL Fug-StB

## Properties

---

- defined and precise positional fixing makes installation easier
- no additional positional stabilisers required
- optimised material distribution to the cold side, creating the perfect rivet head
- top edge of the profile determines the height of the rolled asphalt to be sealed

## Application instructions

---

### Substrate preparation

The joint surfaces must be dry, clean and free from dust and loose debris. Apply primer COLZUMIX®-Haftgrund to both joint faces by brush or spray; avoid overdosing. Allow to dry before placing the tape.

### Application

Position BIGUMA®-Hakenband in the joint so that the hook profile edge aligns with the finished road level — this edge sets the height for the asphalt layers to be rolled. Lightly melt the tape with a propane gas torch and press firmly onto the primed substrate. The innovative cross-sectional shape distributes material optimally toward the cold side of the joint, forming a well-sealed rivet head without additional positional stabilisers.

## Cleaning agents

---

Equipment: BIGUMA®-SWS, petrol or commercial solvents

Skin contact: hand washing paste

## Form of supply

---

28 m per carton, 24 cartons per pallet.

## Technical data

<b>Approvals</b>	TL Fug-StB
------------------	------------

[www.biguma.lt](http://www.biguma.lt) | [info@biguma.lt](mailto:info@biguma.lt)



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.