



# PROXAN®-CP-G

Low-viscosity primer for polysulphide sealants on non-absorbent substrates

---

## Uses

---

Our transparent, low-viscosity primer PROXAN®- CP-G is intended for use on non-absorbent substrates. Whether split clinkers, glazed ceramic, plastic (PVC, polyester, melamine resin), metal (aluminium, steel, copper, zinc) or glass, PROXAN®- CP-G significantly improves the adhesion of the sealant.

## Properties

---

- Alkyl silane based
- Suitable for non-absorbent substrates
- Excellent adhesive properties

## Application instructions

---

### Application

The substrate must be dry, free of dust and grease and without any loose components. Old coatings must be removed. The primer must be uniformly applied using a brush. After a flash-off time of 10 to 30 minutes the sealant can be introduced.

### Material consumption

---

0.005 to 0.01 l per linear metre (depending on joint dimensions)

### Storage

---

Can be stored for 12 months in a dry location at temperatures below +25 °C in a closed original container.

### Form of supply

---

Metal bottle 400 ml: 18 bottles per carton

### Technical data

---

<b>Chemical basis</b>	alkyl silane
<b>Processing time (flash-off time)</b>	10 to 30 minutes
<b>Colour</b>	water clear
<b>Density</b>	approx. 0.8 g/ml
<b>Consumption</b>	0.005-0.01 l/linear m (depending on joint dimensions)

[www.biguma.lt](http://www.biguma.lt) | [info@biguma.lt](mailto:info@biguma.lt)



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.