



PROXAN®-CP-P

Two-component primer for polysulphide sealants on absorbent substrates

Uses

PROXAN®- CP-P is a two-component primer for polysulphide sealants/joint sealants. PROXAN®- CP-P acts like a film on porous, absorbent substrates, such as concrete, brickwork and wood, and creates a homogeneous and sufficiently stable surface for the sealant.

Properties

- EP-resin based
- Suitable for absorbent substrates
- Excellent adhesive properties

Application instructions

Application

The substrate must be dry, free of dust and grease and without any loose components. Mix components A and B thoroughly and apply the primer evenly with a brush. After a flash-off time of 30 minutes to 2 hours (depending on temperature) the sealant can be introduced. The primer must not have fully dried. If more than 24 hours have passed, the old layer must be roughened and new primer applied. Ensure that a film of moisture has not formed on the primer surface due to falling below the dew point temperature.

Weather conditions

Ensure that a film of moisture has not formed on the primer surface due to falling below the dew point temperature.

Material consumption

0.01 to 0.02 l per linear metre (depending on joint dimensions)

Storage

Can be stored for 12 months in a dry location at temperatures below +25 °C in a closed original container.

Form of supply

Combi container per 1 litre (Components A and B): 10 containers per box

Technical data

Chemical basis	epoxy resin
Processing time	approx. 2 to 3 hours
Flash-off time	30 minutes to 2 hours (depending on temperature)
Mixing ratio	A : B = 4 : 1 mass portions
Consumption	0.01 to 0.02 l/linear m (depending on joint dimensions)

www.biguma.lt | info@biguma.lt



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.