



PROXAN®-CP-S

Two-component, sprayable primer for polysulphide sealants on absorbent substrates

Uses

Our two-component primer PROXAN®- CP-S can be applied quickly, as its low viscosity means it can be sprayed. It is particularly suitable for pre-treating porous, absorbent surfaces, such as concrete, brickwork and wood, and is a perfect way to prepare surfaces for the application of the sealant.

Properties

- EP-resin based
- Save time with spraying
- Suitable for absorbent substrates
- Excellent adhesive properties

Application instructions

Application

The substrate must be dry, free of dust and grease and without any loose components. Components A and B are thoroughly mixed and the primer evenly applied to the joint flanks by spraying or using a brush. After a flash-off time of 30 minutes to 2 hours (depending on temperature) the sealant can be introduced. The primer must not have fully dried. If more than 24 hours have passed, the old layer must be roughened and new primer applied.

Storage

Can be stored for 12 months in a dry location at temperatures below +25 °C in a closed original container.

Form of supply

Combination container 1 litre (Components A and B): 10 packs per carton
Combination container 5 litre (Components A and B)

Technical data

Chemical basis	epoxy resin
Processing time	min. 6 hours
Flash-off time	30 minutes to 2 hours (depending on temperature)
Mixing ratio	A : B = 1 : 1 mass portions
Consumption	depending on application method and joint dimensions

www.biguma.lt | info@biguma.lt



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.