



# PROXAN®-FLEXOMAT

Application device for two-component, cold-workable joint sealing compounds

## Uses

The PROXAN®- FLEXOMAT application device is especially designed for applying ready-mixed 25 l containers of pourable polysulphide sealant. With the PROXAN®- FLEXOMAT you can process up to 100 l per hour. The pressure vessel is designed for up to 8 bar and can accommodate containers with up to 25 l contents.

## Properties

- Work can be carried out comfortably while standing
- Easy cleaning

## Application instructions

### Operation

Two workers are required to operate the PROXAN®- FLEXOMAT. One person operates the device and one person guides the provided hand lance. The hose comprises consumable material and is replaced after each use. Cleaning of other parts can be done with PROXAN®- PR-S and PROXAN®- PR 4.

## Technical data

<b>Empty weight</b>	approx. 110 kg
<b>Length</b>	approx. 1,100 mm
<b>Height</b>	approx. 1,300 mm
<b>Width</b>	approx. 580 mm
<b>Motor</b>	HONDA GX 100, 2.1 kW
<b>Max. pressure</b>	8 bar
<b>Container capacity</b>	up to 25 l
<b>Output</b>	up to 100 l/h

[www.biguma.lt](http://www.biguma.lt) | [info@biguma.lt](mailto:info@biguma.lt)



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.