



# DOBAU®-Terrassenband

One-sided adhesive bitumen tape for protection against contact corrosion in wooden terraces

---

## Uses

---

DOBAU®-Terrassenband is the ideal solution for permanently protecting terrace substructures against water, moisture and rot. The self-adhesive sealing tape is easy to apply cold, enabling fast and reliable installation. The top side consists of UV-stable aluminium, providing optimal protection against weathering. The underlying bitumen sealant compound meets the requirements of guideline DTU 51.4 for exterior wooden plank coverings and guarantees the highest quality in professional use.

In addition to protection against water ingress, DOBAU®-Terrassenband offers an additional benefit: it acts as impact sound insulation between the wooden planks, contributing to greater comfort and durability. Thanks to its strong adhesive force, it bonds reliably to wood, metal, plastics and masonry – ideal for versatile applications in terrace construction.

## Properties

---

- simple application
- high flexibility
- impact sound insulating
- UV resistant
- high adhesive force
- self-sealing after application
- optimally matched to the width and length of the planks

## Application instructions

---

### Application

The surface must be resistant to abrasion, grease and dust. Sharp-edged unevenness should be removed where possible. After removing the separating foil, DOBAU®-Terrassenband can be applied to the substructure. The tape must then be pressed on firmly, preferably with a rubber roller. The protruding ends of the tape are pressed down vertically on the sides to provide the best possible protection of the surface. The formation of hollow areas and bubbles must be avoided.

## Storage

---

The product should be protected from direct sunlight and stored at 5 °C to 40 °C. The rolls should also be stored dry and standing on their cut edges. The product is not vulnerable to frost. The properties of DOBAU®-Terrassenband remain unchanged for a long time. Application within 24 months is recommended.

## Form of supply

---

Width: 80 mm; length: 20 m. Further dimensions available on request.

## Technical data

---

<b>Material thickness</b>	1.0 mm
<b>Standard width</b>	80 mm
<b>Standard length</b>	20 m
<b>Ideal application temperature</b>	+5 °C to +40 °C

[www.biguma.lt](http://www.biguma.lt) | [info@biguma.lt](mailto:info@biguma.lt)



This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose.